

# Product overview

Plastic Modular Belt Series



# Straight Running Belt Overview

|  |  |  |   |
|--|--|--|---|
| <p>Pitch 8.00 mm (0.32 in)</p>   | <p>Pitch 12.7 mm (0.50 in)</p>   | <p>Pitch 12.7 mm (0.50 in)</p>   | <p>Pitch 12.7 mm (0.50 in)</p>  |
| <p><b>uni NTB</b><br/>Strength Index (POM)</p> <p>20000 40000 60000</p> <p>2000 N/m (137 lbf/ft)</p>     | <p><b>uni M-OWL</b><br/>Strength Index (POM)</p> <p>20000 40000 60000</p> <p>4500 N/m (309 lbf/ft)</p>     | <p><b>uni M-QNB</b><br/>Strength Index (POM)</p> <p>20000 40000 60000</p> <p>19000 N/m (1302 lbf/ft)</p> | <p><b>uni M-SNB M3</b><br/>Strength Index (POM)</p> <p>20000 40000 60000</p> <p>15000 N/m (1028 lbf/ft)</p>         |
| <p>Pitch 12.7 mm (0.50 in)</p>   | <p>Pitch 19.1 mm (0.75 in)</p>   | <p>Pitch 25.4 mm (1.00 in)</p>   | <p>Pitch 25.4 mm (1.00 in)</p>  |
| <p><b>uni M-TTB</b><br/>Strength Index (POM)</p> <p>20000 40000 60000</p> <p>22500 N/m (1541 lbf/ft)</p> | <p><b>uni Light</b><br/>Strength Index (POM)</p> <p>20000 40000 60000</p> <p>10250 N/m (702 lbf/ft)</p>    | <p><b>uni CNB</b><br/>Strength Index (POM)</p> <p>20000 40000 60000</p> <p>15700 N/m (1076 lbf/ft)</p>   | <p><b>uni JCB Y</b><br/>Strength Index (POM)</p> <p>20000 40000 60000</p> <p>35000 N/m (2400 lbf/ft)</p>            |
| <p>Pitch 25.4 mm (1.00 in)</p>   | <p>Pitch 25.4 mm (1.00 in)</p>   | <p>Pitch 25.4 mm (1.00 in)</p>   | <p>Pitch 25.4 mm (1.00 in)</p>  |
| <p><b>uni LPB</b><br/>Strength Index (POM)</p> <p>20000 40000 60000</p> <p>35000 N/m (2400 lbf/ft)</p>   | <p><b>uni QNB</b><br/>Strength Index (POM)</p> <p>20000 40000 60000</p> <p>35000 N/m (2400 lbf/ft)</p>     | <p><b>uni S-MPB</b><br/>Strength Index (POM)</p> <p>20000 40000 60000</p> <p>23500 N/m (1610 lbf/ft)</p> | <p><b>uni SNB M2</b><br/>Strength Index (POM)</p> <p>20000 40000 60000</p> <p>23500 N/m (1610 lbf/ft)</p>           |
| <p>Pitch 27.9 mm (1.10 in)</p>   | <p>Pitch 38.1 mm (1.50 in)</p>   | <p>Pitch 38.1 mm (1.50 in)</p>   | <p>Pitch 40.0 mm (1.57 in)</p>  |
| <p><b>uni OWL</b><br/>Strength Index (POM)</p> <p>20000 40000 60000</p> <p>12000 N/m (822 lbf/ft)</p>    | <p><b>uni Light EP</b><br/>Strength Index (POM)</p> <p>20000 40000 60000</p> <p>10250 N/m (703 lbf/ft)</p> | <p><b>uni SSB</b><br/>Strength Index (POM)</p> <p>20000 40000 60000</p> <p>36000 N/m (2467 lbf/ft)</p>   | <p><b>uni ACB</b><br/>Strength Index (POM)</p> <p>20000 40000 60000 80000 100000</p> <p>90000 N/m (6169 lbf/ft)</p> |



# Straight Running Belt Overview




**uni L-SNB**  
Strength Index (POM)




**uni OPB**  
Strength Index (POM)





**uni BLB**  
Strength Index (POM)




**uni CPB**  
Strength Index (POM)





**uni CSB**  
Strength Index (POM)




**uni ECB**  
Strength Index (POM)




**uni MPB**  
Strength Index (POM)




**uni RTB M1**  
Strength Index (POM)



**uni X-MPB**  
Strength Index (POM)




**uni XLB**  
Strength Index (POM)





For further information,  
please find the latest  
version of our modular  
datasheets at:  
[www.unichains.com](http://www.unichains.com)



# Side Flexing Belt Overview





**uni Flex ASB**  
Strength Index (POM)




**uni Flex OSB**  
Strength Index (POM)




**uni Flex SNB**  
Strength Index (POM)




**uni Flex ONE**  
Strength Index (POM)



**uni Flex L-ASB**  
Strength Index (POM)



**uni Flex L-OSB**  
Strength Index (POM)



Expert advice, quality solutions and local service for all your belting needs  
[www.ammeraalbeltech.com](http://www.ammeraalbeltech.com)

**Global Headquarters:**  
**Ammeraal Beltech Holding B.V.**  
P.O. Box 38, 1700 AA Heerhugowaard  
The Netherlands

T +31 72 575 1212  
F +31 72 571 6455  
info@ammeraalbeltech.com

This information is subject to alteration due to continuous development. Ammeraal Beltech will not be held liable for the incorrect use of the above stated information. This information replaces previous information. All activities performed and services rendered by Ammeraal Beltech are subject to general terms and conditions of sale and delivery, as applied by its operating companies.